

# ROP400

## Spray Adhesive

### Manufacturer

#### Roppe Corporation

1602 N. Union Street

P.O. Box 1158

Fostoria, Ohio USA 44830-1158

t: (419) 435.8546 tf: (800) 537.9527 f: (419) 435.1056

e-mail: [sales@roppe.com](mailto:sales@roppe.com)

[www.roppe.com](http://www.roppe.com)



### DESCRIPTION

Roppe ROP400 Adhesive for Vinyl Tile is a no VOC, non-flammable water based adhesive formulated for use with Roppe Vinyl and Laminate Tiles. The immediate high sheer strength allows for foot traffic after installation and eliminates the worry of adhesive displacement due to early traffic. ROP400 for Vinyl Tile reduces the amount of adhesive on projects by up to 80%, therefore reducing the amount of weight during shipment and manufacturing. ROP400 Adhesive for Vinyl Tile canisters are completely recyclable and the design allows for the complete use of the contents, so there is no waste.

**COLOR:** White

**PACKAGING:** 22 ounce Aluminum Cans, 6 Cans per Case with Hand Lever

**WEIGHT:** 8.25 Pounds per Case

**TROWEL SIZE:** No Trowel Needed

**COVERAGE:** 150 – 190 Square Feet per Can

**RECOMMENDED SUBSTRATES:** Recommended for properly prepared Concrete, Wood, Metal and Fiberglass

### MOISTURE AND PH REQUIREMENTS

ASTM F 1869; Calcium Chloride, 7.0 lbs

ASTM F 2170; Relative Humidity, 85%

pH; 11 or less

### PRODUCTS

Designed to install Northern Timbers, Northern Leathers & SafeTcork Vinyl Tile.

### CLEAN UP

Remove any adhesive from surface of materials with a soft clean cloth with warm soapy water, while the adhesive is still wet. If adhesive has dried, gently clean the surface with a soft clean cloth with denatured alcohol.

### CALCULATED VOC's

0 Grams per Liter of Coating

### LIMITATIONS

All Traffic, Immediately

Heat Welding, After 3 Hours

Maintenance, after 48 Hours

Not for use over existing floor covering or old adhesives

Not for use outdoors

**SHELF LIFE:** Shelf life is two years when stored at 70° F (21° C) in an unopened container

**FREEZE THAW STABILITY:** Protect material from freezing

**QUALIFICATIONS:** FloorScore, CHPS and LEED Compliant

As not all information can be covered within this general guide, please refer to the appropriate Product Data Sheets, Installation and/or Maintenance Instructions for additional detailed information. Obtain from [www.roppe.com](http://www.roppe.com) by clicking the Technical Support link, or by contacting Roppe Customer Service @ 800-537-9527.

