

ROP500

Spray Adhesive

Manufacturer

Roppe Corporation

1602 N. Union Street

P.O. Box 1158

Fostoria, Ohio USA 44830-1158

t: (419) 435.8546 tf: (800) 537.9527 f: (419) 435.1056

e-mail: sales@roppe.com

www.roppe.com



DESCRIPTION

Roppe ROP500 Adhesive for Rubber Tile is a no VOC, non-flammable water based adhesive formulated for use with Roppe Rubber Tiles. The immediate high shear strength allows for foot traffic after installation and eliminates the worry of adhesive displacement due to early traffic. ROP500 Adhesive for Rubber Tile reduces the amount of adhesive on projects by up to 80%, therefore reducing the amount of weight during shipment and manufacturing. ROP500 for Rubber Tile canisters are completely recyclable and the design allows for the complete use of the contents, so there is no waste.

COLOR: White

PACKAGING: 22 ounce Aluminum Cans, 6 Cans per Case with Hand Lever

WEIGHT: 8.25 Pounds per Case

TROWEL SIZE: No Trowel Needed

COVERAGE: 125 – 150 Square Feet per Can

RECOMMENDED SUBSTRATES: Recommended for properly prepared Concrete, Wood, Metal and Fiberglass

MOISTURE AND PH REQUIREMENTS

ASTM F 1869; Calcium Chloride, 7.0 lbs

ASTM F 2170; Relative Humidity, 85%

pH; 11 or less

PRODUCTS

Designed to install our Rubber Tile Lines (RCD, Smooth, Fiesta®, SafeTcork® and Dimensions), Recoil & Tuflex.

CLEAN UP

Remove any adhesive from surface of materials with a soft clean cloth with warm soapy water, while the adhesive is still wet. If adhesive has dried, gently clean the surface with a soft clean cloth with denatured alcohol.

CALCULATED VOC's

0 Grams per Liter of Coating

LIMITATIONS

All Traffic, Immediately

Heat Welding, After 3 Hours

Maintenance, after 48 Hours

Not for use over existing floor covering or old adhesives

Not for use outdoors

SHELF LIFE: Shelf life is two years when stored at 70° F (21° C) in an unopened container

FREEZE THAW STABILITY: Protect material from freezing

QUALIFICATIONS: FloorScore, CHPS and LEED Compliant

As not all information can be covered within this general guide, please refer to the appropriate Product Data Sheets, Installation and/or Maintenance Instructions for additional detailed information. Obtain from www.roppe.com by clicking the Technical Support link, or by contacting Roppe Customer Service @ 800-537-9527.

