

Roppe BaseMates™ Wall Base



Product Data

Section 9
Resilient Flooring



Architects' Material Specifications

Roppe BaseMates™

BaseMates™ shown in the finish schedule or listed herein as BaseMates™ shall be Roppe 1/8" (3.175mm) to 5/16" (7.93mm) thick (straight & concaved foundation when applicable) and will be Type TS Thermoset Extruded Vulcanized Rubber furnished by Roppe Corporation, Fostoria, Ohio. Each shall be constructed of first-quality materials and shall be smooth and free from imperfections which detract from its appearance. The base shall conform fully to the requirements of Standard Specifications F-1861, Type TS (Thermoset Vulcanized Rubber), Group 1 (solid). BaseMates shall be 3/4" (19.05mm), 1-1/8" (28.575mm) and 1-3/4" (44.45mm) in height and in rolls 60ft. (18.288m) in lengths with unique identical colored divider which easily detaches generating two-60 ft. pieces (120 ft. total per rolls – 36.576m); and in the color stated _____.

Roppe Rubber Corner Blocks

Roppe Rubber Corner Blocks shown in the finish schedule or listed herein as Roppe Rubber Corner Blocks shall be 1/2" (25.4mm) from finish corner to edge and will be Type TS Thermoset Extruded Vulcanized Rubber furnished by Roppe Corporation, Fostoria, Ohio. Each shall be constructed of first-quality materials and shall be smooth and free from imperfections which detract from its appearance. The corner shall conform fully to the requirements of Standard Specifications F-1861, Type TS (Thermoset Vulcanized Rubber), Group 1 (solid). Rubber Corner Blocks shall be _____ (inside or outside preference inserted) and _____ (custom size inserted) in length and in the color stated _____.

7-09

