

Roppe Metal Stair Treads



Product Data

Section 9

Resilient Flooring



Architects' Material Specifications

Architects' Material Specifications – ROPPE METAL STAIR TREADS

All aluminum treads shown in the finish schedule or listed in this specification for heavy traffic areas shall be Roppe Metal Stair Treads as furnished by Roppe Corporation, Fostoria, Ohio. Roppe Metal Stair Treads aluminum base shall be constructed of heat treated exterior grade aluminum 6063T3 and filled with a UV stable, chemical resistant closed cell anti-slip epoxy coating combined with mineral abrasive grits that are uniform through-out providing anti-slip properties and construction of first quality materials, and shall be smooth and free of imperfections which detract from its appearance and contain no asbestos fiber. Roppe Metal Stair Treads shall be .250" (6.35 mm) nominal thickness, shall conform to industry standards. Roppe Metal Stair Treads shall be .250" (6.35mm) in nominal thickness, ____ (mm) in nominal depth, _____ (mm) in nominal length and in either single color or color combinations _____ stated.

Architects' Material Specifications – ROPPE METAL STAIR TREAD NOSING & METAL FLAT STEP

All aluminum stair tread nosing and metal flat step shown in the finish schedule or listed in this specification for heavy traffic areas shall be Roppe Metal Stair Nosing and/or Roppe Metal Flat Step as furnished by Roppe Corporation, Fostoria, Ohio. Roppe Metal Stair Nosing & Roppe Metal Flat Step's aluminum base shall be constructed of heat treated exterior grade aluminum 6063T3 and filled with a UV stable, chemical resistant closed cell anti-slip epoxy coating combined with mineral abrasive grits that are uniform through-out providing anti-slip properties and construction of first quality materials, and shall be smooth and free of imperfections which detract from its appearance and contain no asbestos fiber. Roppe Metal Stair Tread Nosing and Metal Flat Step shall be 0.22" in nominal thickness, ____ (mm) in nominal depth, _____ (mm) in nominal length and in either single color or color combinations _____ stated.

