

Metal Tread

flat step (no nose)
MADE IN THE USA
PRODUCT SUBMITTAL



1. Manufacturer
Roppe Corporation
1602 N. Union Street
P.O. Box 1158
Fostoria, Ohio USA 44830-1158
t: (419) 435.8546 tf: (800) 537.9527
f: (419) 435.1056
e-mail: sales@roppe.com
www.roppe.com



2. Product Description
Roppe Metal Stair Treads, Metal Stair Tread Nosings & Metal Flat Step are constructed of heat treated exterior grade aluminum 6063T3 which is resistant to corrosion. The inlaid anti-slip epoxy color coating is color fast and is available in eight standard colors which can be used in combination to generate numerous color themes due to the dual channel face design. ROPPE treads are created using material which makes the tread resistant to marring, scratching and chipping. Roppe Metal Stair Treads, Metal Nosings & Metal Flat Steps are supplied pre-drilled with countersunk holes from the factory for a flush finish with mechanical fasteners.

Metal Flat Step (No Nose) Dimensions:
Depth: 7" Nominal
Overall Thickness: Nominal 0.22"
Length: 1 foot to 10 feet nominal lengths
Available Colors: Standard Colors (one color only).

Special Order Dimensions:
Sizes: Available in lengths up to 144" (3.667.6mm) nominal.
Special Order Depths: 7.5" (109.5mm) and 11" (279.4mm) nominal.
Overall Thickness: Nominal .25" (6.35mm)
Special Order Minimums: None
Nose Profile: 90 degree square nose.
No returns will be accepted for custom, standard or stocking colors or for incorrectly measured material.
Standard Non-Stocking Colors: Grey, Yellow, Green, Blue, Red, Black and Brown (Single Color or Combinations)
Lead Time: 3 weeks.
Minimum Orders: No minimum order requirements.
Customer Colors available for an additional charge.
Minimum Custom Color Orders: No minimum order required
Custom Color Lead Time: 3 weeks.

Custom Color Matching: Available upon request for additional charge. All custom match colors require customer color sample submittal, approval and signoff prior to manufacturing. Once approval and signoff has been completed, order led time will be approximately three (3) weeks. No returns will be accepted for custom, standard or stocking colors or for incorrectly measured material.

- 3. Technical Data**
Metal Stair Treads, Metal Stair Nosing and Metal Flat Step
- **ASTM E 648 (NFPA 253),** Critical Radiant Flux: Class 1, >1.00 W/cm²
 - **ASTM E 662 (NFPA 258),** Specific Optical Density of Smoke Generated by Solid Materials: Passes, < 450
 - **ASTM D 2047,** Static Coefficient of Friction (Slip Resistance): Exceeds A.D.A recommendations of > 0.60 for flat surfaces & > 0.80 for ramps using Neolite sensors.
 - **A.D.A Visually-Impaired:** Yellow and Black color combination treads meet A.D.A recommendations for contrasting colors.
 - **Passes:** California State Code Title 24 for clearly contrasting color combinations.

4. Installation* (Visit roppe.com for complete Installation instructions)
All materials are to be delivered to the installation location in its original packaging with labels intact. Store products in a dry area protected from the weather on a smooth, flat, dry surface with temperatures maintained between 65°F (19°C) and 85° F (30°C). Remove all plastic wrapping and strapping from the pallets or cartons prior to installation. DO NOT stack either the treads or tread cartons! The installation area, substrate, mechanical fasteners, treads and adhesive are to be maintained between 65° F (19°C) and 85° F (30°C) for at least 48 hours before installation, during installation, and 48 hours after the installation. Inspect all material for proper type, proper mechanical fasteners, tread size, color, thickness, and quality.

Adhesives
Premium Grade Exterior Grade Polyurethane Adhesive and Application. A Premium grade exterior polyurethane adhesive approved by the adhesive manufacturer for bonding aluminum directly to concrete, exterior grade plywood or metal is required and can be obtained at most major home center stores.

5. Maintenance* (Visit roppe.com for complete Maintenance instructions)
Sweep to remove dirt and other particulate. ROPPE Metal Stair Treads, Metal Stair Nosings and Metal Flat Step should be cleaned periodically to maximize the life and appearance of the material.

6. Availability and Cost
Products are available through Roppe distributors. Contact Roppe Customer Service (800) 537-9527 or visit www.roppe.com.

7. Technical Assistance
Technical service information and assistance may be obtained by calling Roppe Customer Service at 1-800-537-9527, or by visiting www.roppe.com.
Samples may be obtained by may be obtained by calling Roppe Customer Service at 1-800-537-9527, or by visiting www.roppe.com.

8. Limited Warranty
Roppe Corporation manufactures and markets its floor products under the trade name Roppe is warranted for a period of one (1) year from date of installation to be free of defects in material and workmanship. Roppe has a five (5) year Limited Wear Warranty on Metal Stair Treads, Metal Stair Nosings and Metal Flat Step if installed, maintained, and used strictly in accordance with Roppe's written instructions.

***For complete installation and maintenance instructions visit www.roppe.com.**

