

Product Data

Section 9

Resilient Flooring



Maintenance

Initial Maintenance

Allow 48 hours after installation for proper curing of the adhesives. Remove any coverings used for floor protection after installation prior to cleaning. Sweep, dust mop and/or vacuum floor to remove any dirt or particulates accumulated on the floor. Clean the floor with a high quality Vinyl Floor cleaner such as Bona® Stone, Tile & Laminate Floor Cleaner or for large areas us an Auto Scrubber with White Pads and a mild solution of Neutral pH cleaner such as Spartan Chemicals Green Solutions All Purpose Cleaner or Spartan Chemicals Clean by Peroxy. Do not use detergents, abrasive cleaners or “mop and shine” products as they will dull the look of the floor. Do not use vacuums with a beater bar or electric brooms with hard plastic bottoms and no padding as this may cause discoloration, scratching and loss of gloss.

Daily Maintenance

Sweep, dust mop and/or vacuum floor to remove any dirt or particulates accumulated on the floor. Remove any spills or other large deposits of dirt and / or debris

Weekly Maintenance

Keep in mind, if the appearance of the flooring becomes unacceptable; this procedure may require completion more frequently to provide acceptable appearance. Sweep, dust mop and/or vacuum floor to remove any dirt or particulates accumulated on the floor. Clean the floor with a high quality Vinyl Floor cleaner such as Bona® Stone, Tile & Laminate Floor Cleaner or for large areas us an Auto Scrubber with White Pads and a mild solution of Neutral pH cleaner such as Spartan Chemicals Green Solutions All Purpose Cleaner or Spartan Chemicals Clean by Peroxy. Do not use detergents, abrasive cleaners or “mop and shine” products as they will dull the look of the floor. Do not use vacuums with a beater bar or electric brooms with hard plastic bottoms and no padding as this may cause discoloration, scratching and loss of gloss

Floor Protection Devices

When moving in appliances or heavy furniture, it is always wise to protect the floor from scuffing and tears by using something to protect the floor. Use floor protectors under furniture or fixtures to reduce indentation; as a rule of thumb, the heavier the item the wider the floor protection device needed. Place walk-off mats at outside entrances manufactured with non-staining backs to prevent discoloration

1-11

