

# Roppe Pinnacle/Pinnacle Plus Wall Base



## Product Data

Section 9

Resilient Flooring



## Architects' Material Specifications

### PINNACLE RUBBER BASE

Flooring accessories shown in the finish schedule or listed herein as Cove Base or Wall Base shall be 1/8" (3.175mm) thick Type TS, Thermoset Vulcanized Pinnacle EXTRUDED RUBBER WALL BASE as manufactured by Roppe Corporation, Fostoria, Ohio. It shall be constructed of first quality materials, properly vulcanized, and shall be smooth and free from imperfections which detract from its appearance. The base shall conform fully to all the requirements of Standard Specification F-1861, Type TS (Thermoset Vulcanized Rubber), Group 1 (solid). All Wall Base shall be of the type (Straight, Style A, or Cove, Style B), with a nominal height of (2-1/2" {63.5mm}, 3" {76.2mm}, 3-1/2" {88.9mm}, 4" {101.6mm}, 4-1/2" {114.3mm}, 5" {127.0mm} and 6" {152.4mm}) \_\_\_\_\_, in nominal lengths of (48" {1.22m}, or 120 ft. {36.576m}) \_\_\_\_\_, in the color stated \_\_\_\_\_, and 1/8" (3.175mm) nominal thickness.

Sanitary Wall Base shall be 4" (101.6mm) high with a 2" (50.8mm) Sanitary Toe. The toe shall be 1/8" (3.175mm) nominal thick. The length shall be (48" {1.22m} ) nominal long and in the color selected

### PINNACLE *PLUS* RUBBER BASE

Flooring accessories shown in the finish schedule or listed herein as Cove Base or Wall Base shall be 1/8" (3.175mm) thick Type TS, Thermoset Vulcanized Pinnacle *Plus* EXTRUDED RUBBER WALL BASE as manufactured by Roppe Corporation, Fostoria, Ohio. It shall be constructed of first quality materials, properly vulcanized, and shall be smooth and free from imperfections which detract from its appearance. The base shall conform fully to all the requirements of Standard Specification F-1861, Type TS (Thermoset Vulcanized Rubber), Group 1 (solid). All Wall Base shall be of the style \_\_\_\_\_ (style B, Base Shoe or Cove), with a height of 4" (101.6mm) nominal, in the color stated \_\_\_\_\_, and 1/8" (3.175mm) nominal thickness. The length shall be either 60 ft. (18.288m) nominal for base shoe profile or 120 ft. (36.576m) nominal long for standard toe design \_\_\_\_\_, and in the color selected.

7-09

