



**1. Manufacturer**

**Roppe Corporation**  
1602 N. Union Street  
P.O. Box 1158  
Fostoria, Ohio USA 44830-1158  
t: (419) 435.8546 tf: (800) 537.9527 f: (419) 435.1056  
e-mail: sales@roppe.com [www.roppe.com](http://www.roppe.com)

**2. Product Description**

Roppe Pinnacle Rubber Base is designed for use in commercial and residential wall base applications. PVC free Roppe Pinnacle Base is the professional's choice, because 100% Type TS Pinnacle rubber base is highly durable and extremely flexible, allowing for easy installations around columns, corners and architectural curves.

**Base Toe Profiles:** Standard, No Toe, Butt Toe – 5/8"

Long Toe 1" and Sanitary Toe Base 2" (all nominal)

**Gauge:** 1/8" nominal (3.175mm)

**Heights:** 2 1/2", 3", 3 1/2", 4", 4 1/2", 5", 5 1/2", 6"

Butt Toe, Long Toe and Sanitary Toe: Only available in 4" heights

**Styles:** Available in coved and straight styles in 2 1/2", 4" and 6" nominal heights. Additional nominal heights: 3", 3 1/2", 4 1/2", 5" and 5 1/2" available in cove only. Minimum order required.

**Sizes:** Available in 48" (1.22m) lengths & 120 ft. (36.576m) coils

**Inside & Outside Corner Blocks**

**Gauge:** Nominal 1/2" (12.770mm)

**Width:** Nominal 1" (25.4mm)

**Height:** Available in all heights matching Pinnacle wall base heights.

**Rubber Corner Blocks Height:** Custom order height as needed. Roppe recommends that corner blocks are ordered at least 1/4" taller than the finished height of the wall base that it will be used with. Any necessary corner height reductions can be achieved by simply trimming the bottom end of the corner block.

**Colors:** Available in all 70 colors that coordinate with Pinnacle wall base.

**Inside and Outside Rubber Corner Blocks Attached Wings**

**Gauge:** Nominal 0.060"-0.080"

**Wing Width:** 1" each side of corner block

**Height:** Available in all heights matching Pinnacle wall base heights.

**Rubber Corner Blocks Height:** Custom order height as needed. Roppe recommends that corner blocks are ordered at least 1/4" taller than the finished height of the wall base that it will be used with. Any necessary corner height reductions can be achieved by simply trimming the bottom end of the corner block.

**Colors:** Available in all 70 colors that coordinate with Pinnacle wall base.

**Pinnacle Rubber Base Inside & Outside Factory Corners**

**Gauge:** 1/8" (3.165mm) nominal for all factory corners

**Length:** Inside and Outside Factory Returns, all Nominal

**IC Standard Toe Inside:** 2-1/4" nominal length of return. Sizes 2-1/2", 4" and 6".

**OC Standard Toe Outside:** 2-1/4" nominal length of return. Sizes 2-1/2", 4" and 6".

**NT OC No Toe Outside:** 2-1/4" nominal length of return. Sizes 2-1/2", 4" and 6".

**UL OC Underlap Outside:** 3" nominal including underlap


**LT OC Long Toe Outside:** 2-1/4" Nominal, Size 4" nominal

**Sanitary Toe Corner Outside:** 3-3/4" nominal, Size 4" nominal

**No Toe:** Adds a decorative touch to carpeted interiors

**Long Toe:** Extends 1" to cover wide irregularities between floor and wall.

**Sanitary Toe:** High safety or hygienic application. The 2" toe butts up against our rubber tile, eliminating possible base-to-tile overlaps/gaps.



**3. Technical Data**

Roppe Pinnacle Base meets Standard Specification F-1861 Type TS (Thermoset Vulcanized Rubber), Group 1 (solid).

- **Flexibility:** No crack or break (1/4 in. mandrel) ASTM F-137
- **Resistance to Light:** Average DE not greater than 8.0 ASTM F-1515;
- **Dimensional Stability:** No more than ± 0.25% ASTM F-1861;
- **Resistance to Chemicals:** No more than a slight change in surface dulling, surface attack or staining ASTM F-925;
- **Critical Radiant Flux of Floor Covering Systems:** Class 1, >0.45 W/cm<sup>2</sup> ASTM E 648 (NFPA 253);
- **Specific Optical Density of Smoke Generated by Solid Materials:** Passes, < 450 ASTM E 662 (NFPA 258);
- **Surface Building Characteristics of Building Materials:** Class C ASTM E 84 (NFPA 255).

**4. Installation\*** ([Visit roppe.com for complete Installation instructions](http://www.roppe.com))

All material is to be delivered to the installation location in its original packaging with labels intact. The installation area, unboxed wall base and adhesive are to be maintained between 65° (19°C) and 85° (30°C) for at least 48 hours before installation, during installation and thereafter. Proceed with the installation only when the conditions are proper and correct. Inspect all material for proper type and color. A bond test should be performed at least 72 hours prior to the scheduled installation to ensure the surface is suitable and there should be extreme difficulty in removing the wall base from the surface.

**Adhesives**

**Roppe 220** Pinnacle Wall Base Adhesive will provide superior bond to our products.

**5. Maintenance\*** ([Visit roppe.com for complete Maintenance instructions](http://www.roppe.com))

Wipe off residue with a smooth clean cloth slightly dampened with cool water, remove the water with a clean soft cloth, and allow the wall base to dry.

**6. Availability and Cost**

Products are available through Roppe distributors. Contact Roppe Customer Service (800) 537-9527 or visit [www.roppe.com](http://www.roppe.com).

**7. Technical Assistance**

Technical service information and assistance may be obtained by calling Roppe Customer Service at 1-800-537-9527, or by visiting [www.roppe.com](http://www.roppe.com).

**Samples** may be obtained by may be obtained by calling Roppe Customer Service at 1-800-537-9527, or by visiting [www.roppe.com](http://www.roppe.com).

**8. Limited Warranty**

Roppe Corporation manufactures and markets its wall base, Pinnacle, which is warranted for a period of (1) year from date of installation to be free of defects in material and workmanship.

**\*For complete installation and maintenance instructions visit [www.roppe.com](http://www.roppe.com).**

