

# Pinnacle Plus

wall base

MADE IN THE USA

PRODUCT QUICK SPEC



# ROPPE.

Proven. Flooring. Experiences.

## 1. Manufacturer

### Roppe Corporation

1602 N. Union Street

P.O. Box 1158

Fostoria, Ohio USA 44830-1158

t: (419) 435.8546 tf: (800) 537.9527 f: (419) 435.1056

e-mail: sales@roppe.com

[www.roppe.com](http://www.roppe.com)

## 2. Product Description

Roppe Pinnacle Plus Rubber Base is designed for use in commercial and residential wall base applications. PVC free Roppe Pinnacle Plus is the professional's choice, because 100% Type TS Pinnacle rubber base is highly durable and extremely flexible, allowing for easy installations around columns, corners and architectural curves. The addition of Pinnacle Plus to the Pinnacle brand includes 15 new attractive designs and can be installed in conjunction with Roppe's unique Rubber Corner Blocks creating a clean corner look.

**Profiles:** 00, 10, 15, 50, 90 and 95 with base shoe/unique toe

**Gauge:** 1/8" nominal (3.175mm)

**Height:** 4" (101.6mm); 15 and 95 are nominal 5" (127.0mm)

**Sizes:** Packaged in 60ft. (18.288m) coils

**Profiles:** 20 and 30 with cove

**Gauge:** 1/8" nominal (3.175mm)

**Height:** 4" (101.6mm)

**Sizes:** Packaged in 120ft. (36.576m) coils

**Profiles:** 25 and 35

**Gauge:** 1/4" nominal (6.35mm)

**Height:** 4-9/16" (115.8mm) nominal

**Sizes:** Packaged in 60 ft. (18.288m) coils

**Profile:** 55

**Gauge:** 3/8" (.375mm) Nominal

**Height:** 5 1/2" (139.7mm)

**Sizes:** Packaged in 48' ft carton

**Profile:** 65

**Gauge:** 3/8" (.375mm) Nominal

**Height:** 4 5/8" (117.48mm)

**Sizes:** Packaged in 48' ft carton

**Profile:** 75

**Gauge:** 3/8" (.375mm) Nominal

**Height:** 3" (76.2mm)

**Sizes:** Packaged in 48' ft carton

**Profile:** 85

**Gauge:** 1/4" (6.35mm) Nominal

**Height:** 4 1/4" (107.95mm)

**Sizes:** Packaged in 60 ft. (18.288m)

## Inside & Outside Corner Blocks

**Gauge:** Nominal 1/2" (12.770mm)

**Width:** Nominal 1" (25.4mm)

**Height:** Available in all heights matching Pinnacle wall base.

**Rubber Corner Blocks Height:** Custom order height as needed. Roppe recommends that corner blocks are ordered at least 1/4" taller than the finished height of the wall base that it will be sued with. Any necessary corner height reductions can be achieved by simply trimming the bottom end of the corner block.

**Colors:** Available in all 70 colors that coordinate with Pinnacle wall base.

## Inside and Outside Rubber Corner Blocks Attached Wings

**Gauge:** Nominal 0.060"-0.080"

**Wing Width:** 1" each side of corner block

**Height:** Available in all heights matching Pinnacle wall base heights.

**Rubber Corner Blocks Height:** Custom order height as needed. Roppe recommends that corner blocks are ordered at least 1/4" taller than the finished height of the wall base that it will be sued with. Any necessary corner height reductions can be achieved by simply trimming the bottom end of the corner block.

**Colors:** Available in all 70 colors that coordinate with Pinnacle wall base.

## 3. Technical Data

Roppe Pinnacle Plus meets Standard Specification F-1861 Type TS (Thermoset Vulcanized Rubber), Group 1 (solid).

- **Flexibility:** No crack or break (1/4 in. mandrel) ASTM F-137
- **Resistance to Light:** Average DE not greater than 8.0 ASTM F-1515
- **Dimensional Stability:** No more than  $\pm 0.25\%$  ASTM F-1861
- **Resistance to Chemicals:** No more than a slight change in surface dulling, surface attack or staining ASTM F-925
- **Critical Radiant Flux of Floor Covering Systems:** Class 1,  $>0.45$  W/cm<sup>2</sup> ASTM E 648 (NFPA 253)
- **Specific Optical Density of Smoke Generated by Solid Materials:** Passes,  $< 450$  ASTM E 662 (NFPA 258)
- **Surface Building Characteristics of Building Materials:** Class C ASTM E 84 (NFPA 255).

## 4. Installation\* (Visit [roppe.com](http://roppe.com) for complete Installation instructions)

All material is to be delivered to the installation location in its original packaging with labels intact. The installation area, unboxed wall base and adhesive are to be maintained between 65° (19°C) and 85° (30°C) for at least 48 hours before installation, during installation and thereafter. Proceed with the installation only when the conditions are proper and correct. Inspect all material for proper type and color. A bond test should be performed at least 72 hours prior to the scheduled installation to ensure the surface is suitable and there should be extreme difficulty in removing the wall base from the surface.

## Adhesives

**Roppe 205** Wall Base Adhesive is a fortified acrylic emulsion specifically formulated for Roppe Pinnacle Plus which provides excellent initial grab, long term aged bond strength and will not stain light colored walls.

## 5. Maintenance\* (Visit [roppe.com](http://roppe.com) for complete Maintenance instructions)

Wipe off residue with a smooth clean cloth slightly dampened with cool water, remove the water with a clean soft cloth, and allow the wall base to dry.

## 6. Availability and Cost

Products are available through Roppe distributors. Contact Roppe Customer Service (800) 537-9527 or visit [www.roppe.com](http://www.roppe.com).

## 7. Technical Assistance

Technical service information and assistance may be obtained by calling Roppe Customer Service at 1-800-537-9527, or by visiting [www.roppe.com](http://www.roppe.com).

**Samples** may be obtained by may be obtained by calling Roppe Customer Service at 1-800-537-9527, or by visiting [www.roppe.com](http://www.roppe.com).

## 8. Limited Warranty

Roppe Corporation manufactures and markets its wall base, Pinnacle Plus, which is warranted for a period of (1) year from date of installation to be free of defects in material and workmanship.

\*For complete installation and maintenance instructions visit [www.roppe.com](http://www.roppe.com).