

# Roppe Rop-Cord® Rubber Tile



**Product Data**  
Section 9  
Resilient Flooring



## Architects' Material Specification

### VULCANIZED ROP-CORD® RUBBER FLOOR TILE

All floors shown in the finish schedule or listed in this specification for heavy traffic area shall be Roppe Rop-Cord as furnished by Roppe Corporation, Fostoria, Ohio. Rop-Cord® Vulcanized tile shall be homogeneously constructed of select reclaimed commercial tire components, reinforced with a layer of fabric and then vulcanized to a thin rubber backing. Tiles shall be 3/8" nominal thickness, shall conform to industry standards and shall contain no asbestos fiber. Floor covering shall be 12" x 12" (304.8mm x 308.4mm) tiles, and in the color \_\_\_\_\_ (insert color name and number selected).

### NON-VULCANIZED ROP-CORD® RUBBER FLOOR TILE

Rop-Cord Non-Vulcanized tile shall be homogeneously constructed of select reclaimed commercial tile components, reinforced with a polyester non-woven fabric bonded to a thin-adhesive layer. Tiles shall be 3/8" nominal thickness, shall conform to industry standards and shall contain no asbestos fiber. Floor covering shall be 12" x 12" (304.8mm x 308.4mm) tiles, and in the color \_\_\_\_\_ selected (insert color name and number selected).

2-14-10

