

Roppe Rubber Stair Treads Raised and Smooth Profiles



Product Data

Section 9

Resilient Flooring



Architects' Material Specifications

ROPPE RAISED RUBBER STAIR TREADS

All floors shown in the finish schedule or listed in this specification shall be Roppe _____ Raised Design Rubber Stair Treads as furnished by Roppe Corporation, Fostoria, Ohio. Roppe Raised Design Rubber Stair Treads shall be homogeneous in construction of first quality materials, properly vulcanized, and shall be smooth and free of imperfections which detract from its appearance and contain no asbestos fiber. The Rubber Stair Tread shall conform fully to all the requirements of Standard Specification ASTM F-2169, Type TS. Rubber Stair Tread shall be _____ (1/8" {3.175mm}, 3/16" {4.76mm}, 13/64" {5.15mm} or 1/4" {6.35mm}) nominal thickness shall conform to industry standards and shall contain no asbestos fiber. Raised Design Rubber Stair Treads shall be 72" (1.83m) in length, or up to 9' ft. {2.73m} maximum standard in Style #30 Diamond Square Nose, #93 Textured Design and #98 Raised Circular Vantage Design Tread without riser, and in the _____ color shade selected in either square or round nose.

ROPPE ABRASIVE STRIP DESIGN & SMOOTH RUBBER STAIR TREADS

Abrasive Strip Design & Smooth Design Rubber Stair Treads shall be _____ (1/8" {3.175mm}, 3/16" {4.76mm} or 1/4" {6.35mm}) nominal thickness shall conform to industry standards and shall contain no asbestos fiber. Abrasive Strip Design & Smooth Design Rubber Stair Treads shall be _____" (72" {1.83m}) in length and in the _____ color shade selected in either square or round nose.

7-09

