


# vinyl

ACCESSORIES




## nosings




### #202 overlap stair nosing 1/8"

- Square nosing; ribbed safety surface
- Installation Radius: 11 ft.
- 10 12-ft. secs. per ctn. (120 ft.)




### #203 domestic stair nosing 1/8"

- For light-duty applications; installs over vinyl tile or sheet goods
- Installation Radius: 11 ft.
- 5 12-ft. secs. per ctn. (60 ft.)




### #204 undercut carpet nosing 1/4"

- Heavy-duty for 1/4" and 5/16" carpet
- Installation Radius: 11 ft.
- 5 12-ft. secs. per ctn. (60 ft.)



### #206 double undercut stair nosing 1/4"

- For 1/4" and 5/16" carpet
- Installation Radius: 11 ft.
- 5 12-ft. secs. per ctn. (60 ft.)




### #207 vinyl 3/8" butt stair nosing

- 3/8" butt stair nosing for carpet and Rop-Cord™ tile
- Installation Radius: 10 ft., color Black only
- 5 12-ft. secs. per ctn. (60 ft.)




## fillets & tub moldings




### #167 fillet strip

- Superb backing for flashing up the wall color may vary due to 100% recycled content; angle 45°
- Installation Radius: 1 ft.
- 5 20-ft. coils per ctn. (100 ft.)




### #188 cove stick

- Superb backing for flashing up the wall color Neutral only; angle 45°
- Installation Radius: 2 ft.
- 100 5-ft. pcs. per ctn. (500 ft.)



### #189 fillet molding


- Superb backing for flashing up the wall color Snow only; angle 45°
- Installation Radius: 1 ft.
- 25 5-ft. pcs. per ctn. (125 ft.)



### #190 & #191 tub molding 1" (#190) 1-1/2" (#191)


- High-gloss finish, self-stick backing, 1" or 1-1/2" cove for tubs, counters, shelves; colors Snow and Almond only; angle 45°
- Installation Radius: 1 ft.
- 24 5-ft. pcs. per ctn. (120 ft.)

## cove caps




### #158 cove cap (square) 1/4"

- Cap for coved carpets and wall paneling
- Installation Radius: 1 ft.
- 40 12-ft. secs. per ctn. (480 ft.)




### #161 carpet cove trim

- For coved carpet; undercut 3/16" (flexible)
- Installation Radius: 10 ft.
- 20 12-ft. secs. per ctn. (240 ft.)



### #165 cove cap (square) 1/8"


- Cap for coved sheet vinyl; undercut 1/8"
- Installation Radius: 1 ft.
- 50 12-ft. secs. per ctn. (600 ft.)



### #193 vinyl flash cap height: 4"


- Vinyl fillet strip and cove cap in one product; use for vinyl sheet or carpet up to 1/4" thick
- Installation Radius: 4 inches
- 20 5-ft. secs. per ctn. (100 ft.)

## reducers




### #156 glue-down reducer 5/16"

- 5/16" butting gauge undercut; long flange, smooth taper
- Installation Radius: 18 ft.
- 5 12-ft. secs. per ctn. (60 ft.)




### #160 glue-down reducer 3/16"

- Undercut 3/16"; flange and transition combined; smooth transition
- Installation Radius: 10 ft.
- 20 12-ft. secs. per ctn. (240 ft.)




### #168 underslung reducer

- Binder-bar edging for resilient flooring; undercut .115" for use with 1/16" to 1/8" material
- Installation Radius: 3 ft.
- 2 35-ft. coils per ctn. (70 ft.)



### #169 glue-down reducer 1/4"

- 1/4" undercut; long flange, smooth taper
- Installation Radius: 10 ft.
- 5 12-ft. secs. per tube (60 ft.)



### #172 tile reducer 1/8"


- Beveled edge for resilient flooring; 1/8" butting edge
- Installation Radius: 18 ft.
- 50 3-ft. secs. per ctn. (150 ft.)

# vinyl

ACCESSORIES




## reducers (cont.)




### #174 glue-down reducer 1/4"

- Undercut 1/4" with 2" transition
- Installation Radius: 11 ft.
- 10 12-ft. secs. per ctn. (120 ft.)



### #176 multi-use reducer 1/2"

- For carpet, ceramic tile or wood floors
- Installation Radius: 6 ft.
- 10 12-ft. secs. per ctn. (120 ft.)



### #196 carpet reducer 3/8"

- Designed especially for 3/8" carpet
- Installation Radius: 10 ft.
- 10 12-ft. secs. per ctn. (120 ft.)



## wall accessories



### #350 quarter round

- Designed to outperform wood to complement a tread, tile or base job
- 10 12-ft. pieces or 40' coil


## corner guard



### #166 corner guard 1/8" length: 54" (standard)


- 1-1/2" returns; standard length 54" (special order to 9 ft., minimum quantities required)
- Installation Radius: Not Applicable.
- 12 54" pcs. per ctn. (54 ft. on standard orders)

## adapters / transitions



### #152 snap-down divider

- 1-13/32" wide removable section for joining carpets
- Installation Radius: 6 ft.
- 20 12-ft. secs. per ctn. (240 ft.)




### #154 snap-down edging

- 1-9/64" wide removable section for joining carpet to tile
- Installation Radius: 6 ft.
- 20 12-ft. secs. per ctn. (240 ft.)




## adapters / transitions




### #159 tile carpet joiner

- Provides smooth carpet/ tile transition
- Installation Radius: 10 ft.
- 20 12-ft. secs. per tube (240 ft.)




### #175 snap-down edging

- 1-1/4" wide removable section for joining tile to wood
- Installation Radius: 6 ft.
- 20 12-ft. secs. per ctn. (240 ft.)




### #177 tile carpet joiner

- Joins 1/4" carpet to 1/8" tile
- Installation Radius: 10 ft.
- 5 12-ft. secs. per ctn. (60 ft.)



### #179 snap-down super edge

- 1-7/8" wide removable section for joining carpet to wood/ceramic
- Installation Radius: 6 ft.
- 5 12-ft. secs. per ctn. (60 ft.)



### #182 ceramic/wood carpet transition 3/8"

- Molding for joining 5/16" carpet to 3/8" ceramic/wood flooring
- Installation Radius: 12 ft.
- 10 12-ft. secs. per tube (120 ft.)




### #195 feature strip

- Designed to transition between 1/8" tiles or add interest to floor design
- Installation Radius: 3 ft.
- 50 3-ft. pcs. per ctn. (150 ft.)




## adapters / transitions

## tracks



### #155 single flange track

- Works with #152, #154, #175 and #179; color Black only
- Installation Radius: Zero
- 10 12-ft. pcs. per ctn. (120 ft.)



### #178 flexi-track single flange track

- Works with #152, #154, #175 and #179; flexible, contours easily; color Black only
- Installation Radius: 6 ft.
- 20 12-ft. pcs. per ctn. (240 ft.)